

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2002-147615

(43)Date of publication of application : 22.05.2002

(51)Int.Cl.

F16J 15/32

F15B 15/14

(21)Application number : 2000-338874

(71)Applicant : KAYABA IND CO LTD

(22)Date of filing : 07.11.2000


(72)Inventor : IKOMA AKIHISA

(54) BUFFER SEAL

(57)Abstract:

PROBLEM TO BE SOLVED: To achieve correct surface pressure distribution to a slide member in a buffer seal.

SOLUTION: This buffer seal 10 contained in an installation groove to slidably get in contact with a piston rod (the slide member) for reducing pressure fluctuation introduced by a main seal comprises a circular U-groove part 5 to receive hydraulic pressure, a circular slide side lip 1 pressed to the piston rod by hydraulic pressure, a circular heel part 2 facing the opening end side of the installation groove, a circular shoulder part 3 facing a corner part of the installation groove, a circular fixed side lip 4 pressed to a bottom surface of the installation groove by hydraulic pressure, and a circular first inclination surface 11 inclined from the slide side lip 1 to the heel part 2 to gradually get apart from the piston rod. The heel part 2 is continuously curved from the first inclination surface 11.



- 1 滑動側リップ
- 2 ヒール部
- 3 ショルダー部
- 4 固定側リップ
- 5 U溝部
- 10 バッファシール
- 11 第一傾斜面
- 12 第二傾斜面
- 13 活塞杆
- 14 フリット部

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

